



(570)-972-0300

Cables for Every Environment™

Technical Details

SKU or PN :	41110-X
# of Conductors :	12
Conductor Gauge Size :	12 AWG
Conductor Type :	Stranded
Conductor Material :	Tinned Copper
Strand Count :	19
Insulation Material :	Extruded FEP (Fluorinated Ethylene Propylene)
Insulation Thickness (Inches Nom.) :	0.006
Nominal Velocity of Propagation :	69% Nominal
Color Code :	Black/White/Red/Green/Brown/Blue/Orange/Yellow/ Purple/Gray/Pink/Tan
Shield (Y N) :	Yes
Shield Type :	Overall Aluminum Foil & Drain Wire
Jacket Material :	Extruded FEP (Fluorinated Ethylene Propylene)
Temperature :	-80°C to 200°C
O.D. (Inches Nom.) :	0.473
Outer Diameter (MM Nom.) :	12.01
Voltage :	300 Volts RMS
Approvals :	(UL) Or ETL CL3P
Weight /LBS per 1000FT:	275
Item Type :	FEP/FEP Cable

*: All data and dimensions are nominal and subject to industry standards and may vary according to plant of manufacture.

**:
Data is provided for informational purposes and does not create a binding obligation nor liability to the seller. Data can change without notice. © All Rights Reserved Ramcorp Technologies LLC.