



Product: [123092A](#)

ControlBus™, Coax RG6, #18 Sol BCCS, PO Ins, QUAD AL Shld, PVC Jkt, AIA Armor, PVC Jkt, CM

Request Sample

Product Description

ControlBus™, Coax RG6 18AWG (Solid) Bare Copper Covered Steel, PO Insulation, Overall Duofoil®+ Aluminum Braid(60%)+Overall Duofoil®+Aluminum Braid(40%) Shield, PVC Inner Jacket, Aluminum Interlock Armor, PVC Outer Jacket, CM

Technical Specifications

Product Overview

Suitable Applications:	exposure to rodent, crush, or cut through force, harsh environment, factory automation, ControlNet™, Modbus II, Industrial Coax, Belden ControlNet cables provide maximum signal integrity and run length exceeding the high-speed, time-critical requirements necessary for ControlNet factory floor applications
------------------------	--

Construction Details

RG Type:	6
----------	---

Conductor

AWG	Stranding	Nom. Diameter	Material
18	Solid	0.0403 in	BCCS - Bare Copper Covered Steel

Insulation

Material	Nom. Diameter
PE - Polyethylene (Foam)	0.178 in

Inner Jacket Material

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.298 in

Outer Shield Material

Layer	Outer Shield Type	Material	Material Trade Name	Coverage
1	Tape	Tri-Laminate (Alum+Poly+Alum)	Duofoil®	100%
2	Braid	Aluminum		60%
3	Tape	Tri-Laminate (Alum+Poly+Alum)	Duofoil®	100%
4	Braid	Aluminum		40%

Armor

Armor Type & Material
AIA - Aluminum Interlock Armor

Outer Jacket Material

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.591 in

Electrical Characteristics

Attenuation

Frequency	Nom. Attenuation [dB/100ft]
1 MHz	0.35 dB/100ft
2 MHz	0.38 dB/100ft
5 MHz	0.45 dB/100ft

10 MHz	0.59 dB/100ft
20 MHz	0.86 dB/100ft
50 MHz	1.37 dB/100ft
100 MHz	1.97 dB/100ft
200 MHz	2.82 dB/100ft
300 MHz	3.48 dB/100ft
400 MHz	4.04 dB/100ft

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Impedence	Nom. Velocity
28 Ohm/1000ft	3.6 Ohm/1000ft	16.2 pF/ft	75 Ohm	82%

Voltage

UL Voltage Rating
300 V RMS

Electrical Characteristics Notes:	SRL Minimum 23dB (5MHz - 50MHz)
-----------------------------------	---------------------------------

Mechanical Characteristics

Temperature

UL Rating	Operating
75°C	-40°C To +75°C

Bend Radius

Stationary Min.	Installation Min.
7.1 in	2.5 in

Bulk Cable Weight:	142 lbs/1000ft
Max. Pull Tension:	200 lbs

Standards and Compliance

Environmental Suitability:	Indoor, Outdoor, Sunlight Resistance
Flammability / Fire Resistance:	UL1685 UL Loading, FT4, 1202
NEC / UL Compliance:	Article 800, CL2, CM
CEC / C(UL) Compliance:	CMG, HL
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	ControlNet is a ControlNet International trademark.
--------	---

History

Update and Revision:	Revision Number: 0.247 Revision Date: 05-26-2021
----------------------	--

© 2021 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.