



Product: [501PTZ](#)

PTZ, RG-59 #20, #22-1pr, #18-2c, Shielded, CM, Siamese

Product Description

PTZ (CCTV + Control + Power) Cable, Rated-CM, 1-RG59 20 AWG solid bare copper with foam polyolefin, 95% bare copper braid, 1-22 AWG stranded bare copper pair with polyolefin insulation and Beldfoil® shield, 2-18 AWG stranded bare copper conductors with PVC insulation, Siamese with PVC jacket

Technical Specifications

Product Overview

Suitable Applications:	Surveillance, CCTV Camera, PTZ (Pan-Tilt-Zoom)
------------------------	--

Physical Characteristics (Overall)

Conductor

Element	AWG	Stranding	Material	Nominal Diameter	No. of Conductors	No. of Coax
Coax(es)	20	Solid	BC - Bare Copper	0.032 in		1
Pair1	22	7x30	BC - Bare Copper	0.03 in	2	
Pair2	18	7x26	BC - Bare Copper	0.047 in	2	

Conductor Count:	5
------------------	---

Insulation

Element	Material	Nominal Diameter
Coax(es)	PE - Polyethylene (Foam)	0.145 in
Pair1	PP - Polypropylene	0.062 in
Pair2	PP - Polypropylene	

Table Notes:	Gas Injected
--------------	--------------

Color Chart

Number	Color
Coax Core	White
Pair1	Blue & White/Blue
Pair2	Black & Red

Color Chart 4

Number	Color
Coax Jacket	Black
Pair1 Jacket	Blue
Pair2 Jacket	White

Inner Shield

Element	Type	Material	Material Trade Name	Coverage [%]	Drainwire AWG	Drainwire Construction n x D
Coax(es)	Braid	Bare Copper (BC)		95%	22	7x30
Pair1	Tape	Bi-Laminate (Alum+Poly)	Beldfoil®	100%		
Pair2	No Shield					

Inner Jacket

Material
PVC - Polyvinyl Chloride

PVC - Polyvinyl Chloride
PVC - Polyvinyl Chloride

Outer Jacket

Material	Nominal Diameter
Banana Peel (No Overall Jacket)	.227 in
	.177 in
	.158 in

Table Notes:	Jacket Material is Same for All Components
--------------	--

Outer Jacket 2

Nominal Diameter
0.419 in

Electrical Characteristics

Conductor DCR

Element	Nominal Conductor DCR	Nominal Inner Shield DCR
Coax(es)	10 Ohm/1000ft	3.5 Ohm/1000ft
Pair1	16 Ohm/1000ft	12 Ohm/1000ft
Pair2	6.5 Ohm/1000ft	

Capacitance

Element	Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Shield
Coax		16.3 pF/ft
Pair1	24 pF/ft	47 pF/ft
Pair2	21.5 pF/ft	

Impedance

Element	Nominal Characteristic Impedance
Coax	75 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.3 dB/100ft
5 MHz	0.65 dB/100ft
10 MHz	0.9 dB/100ft
50 MHz	1.9 dB/100ft
100 MHz	2.6 dB/100ft
200 MHz	3.6 dB/100ft
400 MHz	5 dB/100ft
700 MHz	7 dB/100ft
900 MHz	8 dB/100ft
1000 MHz	8.5 dB/100ft

Delay

Element	Max. Delay Skew	Nominal Delay	Nominal Velocity of Propagation (VP) [%]
Coax	83 ns/100m	1.22 ns/ft	83%

High Frequency

Min. RL (Return Loss) [dB]
24.5 dB

Current

Element	Max. Recommended Current [A]
Coax	
Pair1	5 Amps per Conductor at 25°C
Pair2	

Voltage

UL Voltage Rating
300 V RMS

Temperature Range

Installation Temp Range:	0°C To +75°C
UL Temp Rating:	75°C
Operating Temp Range:	-10°C To +75°C
Separation Temp Range:	0°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	60 lbs/1000ft
Max. Pull Tension:	120 lbs

Standards

NEC Articles:	Article 800
NEC/(UL) Compliance:	CMR
CPR Euroclass:	Fca
RG Type:	59
Other Specification:	Video coax: RG 59/U

Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	Yes
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1666 Vertical Shaft
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	601PTZ

Part Number

Variants

Item #	Color	UPC
501PTZ 0001000	Black, Gray, White	612825155836

Footnote:	C - CRATE REEL PUT-UP.
Patent:	This product has one or more applicable patents. More information on patents can be found at https://www.belden.com/resources/patents .

Product Notes

Notes:	RG59 CCTV + 1 STP22 AWG Control Grade + 2C 18 AWG CMR. Individually jacketed and color coded components, cabled around and each fused to a central binding spline. Cold environment installation: When installing cables that have been stored at ambient temperatures of 32 degrees Fahrenheit (0 degrees Centigrade) or lower, Belden recommends conditioning of the cable for 12 hours at room temperature prior to individual cable leg separation.
--------	---

History

Update and Revision:	Revision Number: 0.360 Revision Date: 09-10-2021
----------------------	--

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.