



Product: [5122FN](#)

Fire Alarm, #14-4c BC, Shielded, NPLF

Product Description

Fire Alarm Cable, Rated-NPLF, 4-14 AWG solid bare copper conductors with PVC/nylon insulation, overall Beldfoil® shield, PVC jacket with ripcord

Technical Specifications

Product Overview

|                        |                                                                                                      |
|------------------------|------------------------------------------------------------------------------------------------------|
| Suitable Applications: | Fire Alarm, Non-Power Limited, Circuits: Audio, Control, Initiating, Notification, Noisy Environment |
|------------------------|------------------------------------------------------------------------------------------------------|

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material         | No. of Conductors |
|-----|-----------|------------------|-------------------|
| 14  | Solid     | BC - Bare Copper | 4                 |

|                  |   |
|------------------|---|
| Conductor Count: | 4 |
|------------------|---|

Insulation

| Material                               | Nominal Wall Thickness |
|----------------------------------------|------------------------|
| PVC/Nylon - Polyvinyl Chloride + Nylon | 0.021 in               |

Color Chart

| Number | Color |
|--------|-------|
| 1      | Black |
| 2      | Red   |
| 3      | Brown |
| 4      | Blue  |

Outer Shield

| Type | Material                | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|------|-------------------------|---------------------|--------------|--------------------|---------------|------------------------------|
| Tape | Bi-Laminate (Alum+Poly) | Beldfoil®           | 100%         | TC - Tinned Copper | 20            | Solid                        |

Outer Jacket

| Material                 | Nominal Diameter | Nominal Wall Thickness | Ripcord |
|--------------------------|------------------|------------------------|---------|
| PVC - Polyvinyl Chloride | 0.348 in         | 0.042 in               | Yes     |

Construction and Dimensions

Cabling

| Twists     |
|------------|
| 3 twist/ft |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR |
|-----------------------|--------------------------|
| 2.46 Ohm/1000ft       | 6.9 Ohm/1000ft           |

Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conductor to Shield |
|-----------------------------------------|---------------------------------------------------------|
| 37.7 pF/ft                              | 67.9 pF/ft                                              |

Current

| Max. Recommended Current [A]   |
|--------------------------------|
| 6.4 Amps per Conductor at 25°C |

Voltage

| UL Voltage Rating |
|-------------------|
| 150 V RMS         |

Temperature Range

|                       |                |
|-----------------------|----------------|
| UL Temp Rating:       | 75°C           |
| Operating Temp Range: | -20°C To +75°C |

Mechanical Characteristics

|                              |                 |
|------------------------------|-----------------|
| Bulk Cable Weight:           | 93.9 lbs/1000ft |
| Max. Pull Tension:           | 212.8 lbs       |
| Min. Bend Radius/Minor Axis: | 3.5 in          |

Standards

|                      |             |
|----------------------|-------------|
| NEC Articles:        | Article 760 |
| NEC/(UL) Compliance: | NPLF        |

Applicable Environmental and Other Programs

|                                   |                               |
|-----------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV):    | Yes                           |
| EU Directive 2003/96/EC (BFR):    | Yes                           |
| EU Directive 2011/65/EU (RoHS 2): | Yes                           |
| EU Directive 2012/19/EU (WEEE):   | Yes                           |
| EU Directive Compliance:          | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                       | Yes                           |
| MII Order #39 (China RoHS):       | Yes                           |

Suitability

|                       |     |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

Flammability, LS0H, Toxicity Testing

|                    |                   |
|--------------------|-------------------|
| UL Flammability:   | UL1685 UL Loading |
| UL voltage rating: | 150 V RMS         |

Plenum/Non-Plenum

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item #         | Color | UPC          |
|----------------|-------|--------------|
| 5122FN 0021000 | Red   | 612825157052 |
| 5122FN 002500  | Red   | 612825157069 |

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.305 Revision Date: 08-27-2021 |
|----------------------|--------------------------------------------------|

at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.