



Product: [1829P](#) 

Broadband Coax, Series 6, 18 AWG Solid BCCS, Foil + 60% AL Braid, Flamarrest® Jkt, CMP

Product Description

Broadband Coax, Series 6, 18 AWG Solid Bare Copper Covered Steel Conductor, FEP Insulation, Foil + 60% Aluminum Braid Shield, Flamarrest® Jacket, CMP

Technical Specifications

Product Overview

|                        |                                                                                                                  |
|------------------------|------------------------------------------------------------------------------------------------------------------|
| Suitable Applications: | Broadband, Cable Television (CATV), RF drop cable, Direct Broadcast Satellite (DBS), Over-The-Air (OTA) antennas |
|------------------------|------------------------------------------------------------------------------------------------------------------|

Construction Details

|              |   |
|--------------|---|
| Series Type: | 6 |
|--------------|---|

Conductor

| AWG | Stranding | Nom. Diameter | Material                         |
|-----|-----------|---------------|----------------------------------|
| 18  | Solid     | 0.040 in      | BCCS - Bare Copper Covered Steel |

Insulation

| Material                                    | Nom. Diameter |
|---------------------------------------------|---------------|
| FEP - Fluorinated Ethylene Propylene (Foam) | 0.170 in      |

Outer Shield

| Layer | Outer Shield Type | Material                      | Material Trade Name | Coverage |
|-------|-------------------|-------------------------------|---------------------|----------|
| 1     | Tape              | Tri-Laminate (Alum+Poly+Alum) | Duobond® II         | 100%     |
| 2     | Braid             | Aluminum                      |                     | 60%      |

Outer Jacket

| Material                 | Nom. Diameter |
|--------------------------|---------------|
| PVC - Polyvinyl Chloride | 0.235 in      |

Electrical Characteristics

Return Loss (RL)

| Frequency [MHz] | Min. Structural Return Loss [dB] |
|-----------------|----------------------------------|
| 5 - 2500 MHz    | 15 dB                            |
| 2500 - 3000 MHz | 10 dB                            |

Attenuation

| Frequency | Nom. Attenuation [dB/100ft] |
|-----------|-----------------------------|
| 1 MHz     | 0.3 dB/100ft                |
| 10 MHz    | 0.7 dB/100ft                |
| 50 MHz    | 1.6 dB/100ft                |
| 100 MHz   | 2.1 dB/100ft                |
| 200 MHz   | 2.9 dB/100ft                |
| 400 MHz   | 4.3 dB/100ft                |
| 700 MHz   | 6.1 dB/100ft                |
| 750 MHz   | 6.4 dB/100ft                |

|          |               |
|----------|---------------|
| 900 MHz  | 7.1 dB/100ft  |
| 1000 MHz | 7.6 dB/100ft  |
| 1450 MHz | 9.6 dB/100ft  |
| 1800 MHz | 11.0 dB/100ft |
| 2250 MHz | 12.7 dB/100ft |
| 3000 MHz | 15.1 dB/100ft |

Electricals

| Nom. Conductor DCR | Nom. Outer Shield DCR | Nom. Capacitance Cond-to-Shield | Nom. Characteristic Impedance | Nom. Velocity |
|--------------------|-----------------------|---------------------------------|-------------------------------|---------------|
| 28 Ohm/1000ft      | 9 Ohm/1000ft          | 16.3 pF/ft                      | 75 Ohm                        | 83%           |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V (CMP)       |

Mechanical Characteristics

Temperature

| Operating    |
|--------------|
| 0°C to +75°C |

Bend Radius

| Installation Min. |
|-------------------|
| 2.4 in            |

|                    |               |
|--------------------|---------------|
| Bulk Cable Weight: | 25 lbs/1000ft |
| Max. Pull Tension: | 150 lbs       |

Standards and Compliance

|                                 |                                                                                                                                  |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Environmental Suitability:      | Indoor - Plenum, Indoor                                                                                                          |
| Sustainability:                 | CA Prop 65                                                                                                                       |
| Flammability / Fire Resistance: | NFPA 262                                                                                                                         |
| NEC / UL Compliance:            | CMP, CATVP                                                                                                                       |
| CEC / C(UL) Compliance:         | CMP                                                                                                                              |
| European Directive Compliance:  | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance:                | China RoHS II (GB/T 26572-2011)                                                                                                  |
| Non-Plenum Number:              | 1829A                                                                                                                            |

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.357 Revision Date: 05-26-2021 |
|----------------------|--------------------------------------------------|

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.