



Product: [3073F](#)

DataTray® 100Ω Twinax, 1 Pr #18 Str TC, PP Ins, OS+TC Brd, PVC Jkt, TC, PLTC, ITC, CMG

Request Sample

Product Description

Twinax 100Ω, 1 Pair 18 AWG (7x26) Tinned Copper, PP Insulation, Overall Beldfoil®+Tinned Copper Braid(55%) Shield, PVC Outer Jacket, TC, PLTC, ITC, CMG

Technical Specifications

Product Overview

Suitable Applications:	harsh environment, IIoT, factory or process automation, video, audio, data communication, etc.
------------------------	--

Construction Details

Conductor

AWG	Stranding	Nom. Diameter	Material
18	7x26	0.046 in	TC - Tinned Copper

Insulation

Material	Color Code	Nom. Diameter	Notes
PP - Polypropylene	White & Blue	0.128 in	Flame Retardant

Outer Shield

Layer	Outer Shield Type	Material	Material Trade Name	Coverage	Notes
1	Tape	Bi-Laminate (Alum+Poly)	Beldfoil®	100%	Foil Out
2	Braid	Tinned Copper (TC)		55%	

Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.388 in

Electrical Characteristics

Attenuation

Frequency	Nom. Attenuation [dB/100ft]
2 MHz	0.41 dB/100ft
10 MHz	1.33 dB/100ft
50 MHz	2.97 dB/100ft
100 MHz	4.20 dB/100ft
200 MHz	5.95 dB/100ft
400 MHz	7.52 dB/100ft

Electricals

Element	Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Cond (Mutual)	Nom. Characteristic Impedance	Nom. Velocity
Pair(s)	6.9 Ohm/1000ft	2.9 Ohm/1000ft	15.3 pF/ft	100 Ohm	65%

Voltage

UL Voltage Rating
600 V (TC), 300 V (CMG, PLTC)

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C Dry, PLTC 75°C Dry/Wet	-40°C to +75°C

Bend Radius

Stationary Min.	Installation Min.
3.2 in (81 mm)	2.4 in

Bulk Cable Weight:	61 lbs/1000ft
Max. Pull Tension:	90 lbs

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, UV Resistance
Sustainability:	CA Prop 65
Flammability / Fire Resistance:	UL1685 UL Loading, FT1, FT4, FT1, FT4
NEC / UL Compliance:	Article 336, Article 725, Article 727, Article 800, CMG, ITC, PLTC, TC
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	Cable contains rod fillers for better electrical performance. CPE Jacket Optional.
--------	--

History

Update and Revision:	Revision Number: 0.353 Revision Date: 10-13-2021
----------------------	--

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.