

Product: [88281](#) 

Precision Video Coax, RG59, #20 Solid BC, Double 98% TC/BC Braid



Product Description

20 AWG solid .032" bare copper conductor, plenum, FEP insulation, tinned copper braid shields (95% coverage), fluorocopolymer jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor				
AWG	Stranding	Material	Nominal Diameter	No. of Coax
20	Solid	BC - Bare Copper	0.032 in	1
Conductor Count:				1

Insulation	
Material	Nominal Diameter
FEP - Fluorinated Ethylene Propylene	0.185 in

Outer Shield			
Type	Layer	Material	Coverage [%]
Braid	1	Tinned Copper (TC)	95%
Braid	2	Tinned Copper (TC)	95%

Outer Jacket	
Material	Nominal Diameter
PVDF - Polyvinylidene Fluoride	0.271 in

Electrical Characteristics

Conductor DCR				
Nominal Conductor DCR	Nominal Conductor DCR	Conductor Resistance	Nominal Outer Shield DCR	Outer Conductor DCR
9.9 Ohm/1000ft	9.9 Ohm/1000ft		1.1 Ohm/1000ft	1.1 Ohm/1000ft

Capacitance	
Nom. Capacitance Conductor to Shield	
19 pF/ft	

Inductance	
Nominal Inductance	
0.125 µH/ft	

Impedance	
Nominal Characteristic Impedance	
75 Ohm	

Return Loss (RL)	
Frequency [MHz]	Minimum Return (RL)
5-216 MHz	27 dB

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.2 dB/100ft
3.6 MHz	0.5 dB/100ft
10 MHz	0.8 dB/100ft
71.5 MHz	2.3 dB/100ft
135 MHz	3.3 dB/100ft
270 MHz	5.1 dB/100ft
360 MHz	6.1 dB/100ft
540 MHz	8 dB/100ft
720 MHz	9.7 dB/100ft
750 MHz	10 dB/100ft
1000 MHz	12.3 dB/100ft

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.43 ns/ft	70%

Voltage

Non-UL Voltage Rating	UL Voltage Rating
2900 V RMS	300 V RMS

Temperature Range

UL Temp Rating:	150°C
Operating Temp Range:	-20°C To +150°C

Mechanical Characteristics

Bulk Cable Weight:	82 lbs/1000ft
Max. Pull Tension:	168 lbs
Min. Bend Radius/Minor Axis:	2.75 in

Standards

NEC/(UL) Compliance:	CMP
CEC/C(UL) Compliance:	CMP
RG Type:	59

Applicable Environmental and Other Programs

Environmental Space:	Outdoor - Direct Burial
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Aerial:	Yes - When supported by messenger wire
Suitability - Burial:	Yes
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

Part Number

Non-Plenum Number:	8281
--------------------	------

Variants

Item #	Color	Put-Up Type	Length	UPC
88281 010500	Black	Reel	500 ft	612825218302
88281 0101000	Black	Reel	1,000 ft	612825216964

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

History

Update and Revision:	Revision Number: 0.333 Revision Date: 09-10-2021
----------------------	--

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.