



Product: [9913F7](#)

50 Ohm Wireless Transmission Coax, RG-8, 10 AWG Str BC, Foil + 90% TC Braid, PVC Jkt, Flexible

Product Description

50 Ohm Wireless Transmission Coax, RG-8, 10 AWG (7x18) Bare Copper Conductor , PE Insulation, Foil + 90% Tinned Copper Braid Shield, PVC Jacket, Flexible

Technical Specifications

Product Overview

Suitable Applications:	Point-to-point and point-to-multipoint wireless antenna communication; Wireless microphones, Two-Way Radios, Amateur (Ham) Radio, Low Power FM, GPS, RFID (Radio Frequency Identification)
------------------------	--

Construction Details

RG Type:	8
----------	---

Conductor

Size	Stranding	Nom. Diameter	Material
10 AWG	7x18	0.108 in	BC - Bare Copper

Insulation

Material	Nom. Insulation Diameter
PE - Polyethylene (Foam)	0.284 in (7.21 mm)

Outer Shield

Layer	Outer Shield Type	Material	Material Trade Name	Coverage
1	Tape	Tri-Laminate (Alum+Poly+Alum)	Duobond® II	100%
2	Braid	Tinned Copper (TC)		90%

Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.405 in (10.3 mm)

Electrical Characteristics

VSWR

Frequency	Max. VSWR
5-2250 MHz	1.43:1

Attenuation

Frequency	Nom. Attenuation
10 MHz	0.6 dB/100ft
50 MHz	1.1 dB/100ft
100 MHz	1.5 dB/100ft
200 MHz	2.0 dB/100ft
400 MHz	3.0 dB/100ft
700 MHz	4.0 dB/100ft
900 MHz	4.7 dB/100ft
1000 MHz	5.0 dB/100ft
2000 MHz	7.5 dB/100ft

2250 MHz	8.0 dB/100ft
3000 MHz	9.8 dB/100ft
4000 MHz	12.1 dB/100ft

Power Rating

Frequency	Max. Power Rating
5 MHz	3,217 W
10 MHz	2,681 W
50 MHz	1,463 W
100 MHz	1,073 W
200 MHz	805 W
400 MHz	575 W
700 MHz	424 W
1,000 MHz	350 W
1,500 MHz	278 W
2,000 MHz	237 W
3,000 MHz	188 W
4,000 MHz	157 W

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
1.1 Ohm/1000ft (3.6 Ohm/km)	1.8 Ohm/1000ft (5.9 Ohm/km)	22.5 pF/ft (73.8 pF/m)	52 Ohm	85%

Voltage

Voltage Rating
300 V

Electrical Characteristics Notes:	Actual Impedance specification is 51.5 +/- 2 ohms.
-----------------------------------	--

Mechanical Characteristics

Temperature

Operating
-40°C to +60°C

Bend Radius

Installation Min.
4.0 in

Max. Pull Tension:	158 lbs (71.7 kg)
Bulk Cable Weight:	96 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor
Sustainability:	CA Prop 65
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.349 Revision Date: 10-27-2021
----------------------	--

Variants

Item #	Color	Putup Type	Length	UPC
9913F7 B59100	Black, Matte	Reel	100 ft	612825261728
9913F7 B59250	Black, Matte	Reel	250 ft	612825261742
9913F7 B59500	Black, Matte	Reel	500 ft	612825261773
9913F7 B591000	Black, Matte	Reel	1,000 ft	612825261735

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.