



Product: [8794](#)

Electronic, 3 C #22 Sol BC, PO Ins, PVC Jkt, CM

Request Sample

Product Description

Electronic, 3 Conductor 22AWG (Solid) Bare Copper, PO Insulation, PVC Outer Jacket, CM

Technical Specifications

Product Overview

Suitable Applications:

low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Conductors
22	Solid	BC - Bare Copper	0.026 in	3

Conductor Count:

3

Insulation

Material	Nominal Wall Thickness
PE - Polyethylene	0.018 in

Color Chart

Number	Color
1	Green
2	Red
3	Yellow

Outer Shield

Material
No Shield

Outer Jacket

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.178 in	0.022 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
16 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor
16 pF/ft

Inductance

Nominal Inductance
0.22 µH/ft

Delay

Nominal Velocity of Propagation (VP) [%]
66%

Current

Max. Recommended Current [A]
3 Amps per Conductor at 25°C

Voltage

UL Voltage Rating
300 V RMS

Temperature Range

UL Temp Rating:	60°C (UL AWM Style 2093)
Operating Temp Range:	-30°C To +60°C

Mechanical Characteristics

Bulk Cable Weight:	21 lbs/1000ft
Max. Pull Tension:	23 lbs
Min. Bend Radius/Minor Axis:	2 in

Standards

NEC/(UL) Compliance:	CM
UL AWM Style Compliance:	UL Style 2093 (300 V 60°C)

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Put-Up Type	Length	UPC
8794 6061000	Gray, Rose	Reel	1,000 ft	612825216520
8794 606U1000	Gray, Rose	UnReel	1,000 ft	612825216513

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

History

Update and Revision:	Revision Number: 0.377 Revision Date: 08-27-2021
----------------------	--

