

Premises Copper > Category 6 > UTP > Plenum > 4 Pairs > 23 AWG

4X23 Category 6 / CMP / White / 1K FT POP™ Box

CMP

Part Number: 77-240-4B

Status: Available



COPPER SPECIFICATIONS

Nominal Velocity of Propagation (%) 73

PHYSICAL CHARACTERISTICS

Nominal Diameter in (mm)	0.21 (5.3)
Nominal Weight lbs/kft (kg/km)	22 (33)
Pallet Quantity (ft)	36000
Package Length	1000
Package Type	POP™ Box

Product Description

Superior Essex Series 77 product line provides exceptional value for jobs that require standards compliant Category 6 cable at a cost-effective price.

Applications

- 10BASE-T through 5GBASE-T Ethernet
- Power over Ethernet (PoE) – IEEE 802.3bt Type 1 to 4
- ATM and token ring


Features

- UL® Certified Environmental Product Declaration (EPD)
- Health Product Declaration™ (HPD™)
- Multi-Attribute Certification by GreenCircle Certified, LLC
- Meets ANSI/TIA-568-C.2 specification
- BrakeBox® payout control system
- CableID® alpha numeric code printed every 2 feet
- QuickCount® marking system in feet and meters
- ColorTip® circuit identification system
- Color coded box labels

Benefits

- Contributes toward 1 LEED point under the Material and Resources credit (MRc)
- Contributes toward 1 LEED point under the MRc
- Offers an overview of the sustainability of a product, its packaging and manufacturing
- Provides cost effective solution
- Adjustable tension control on reel prevents over spin and entangling of cable
- Allows both ends of a cable run to be easily identifiable without the need to separately label or tone the cable
- Provides remaining length of cable on reel
- Easily identifiable conductor mates even in low-light environments
- Easily identifies jacket colors

SUSTAINABILITY CERTIFICATIONS



GENERAL SPECIFICATIONS

Jacket	Flame retardant, low smoke PVC
Jacket Color	White
End User Application	Enterprise, Residential, LAN
Environment	Indoor
Standards Compliance	UL 444 CSA C22.2 No.214-08 UL 1666 ANSI/TIA-568.2-D
NRTL Programs	UL Verified CAT 6 UL, c(UL) Listed CMP

COPPER SPECIFICATIONS

Pair Count	4
Conductor	Solid annealed copper
Conductor Count	8
AWG (mm)	23 (0.57)
Insulation	FEP
Insulation Colors	Color Tip®: Light Blue, Blue, Light Orange, Orange, Light Green, Green, Light Brown, Brown
Characteristic Impedance (Ohms)	100 ± 15
Voltage Rating	300

