



(570)-972-0300

[Cables for Every Environment™](#)

Technical Details

SKU or PN :	XLPCPE-TC-14/25
# of Conductors :	25
Conductor Gauge Size :	14
Conductor Type :	Stranded Bare Copper
Conductor Material :	Bare Copper
Strand Count :	7 (Annealed Bare Copper per ASTM B-8)
Insulation Material :	XLP (Cross Linked Polyethylene)
Insulation Thickness (Inches Nom.) :	0.03
Color Code :	ICEA Method 1 - Table E-2
Shield (Y N) :	No
Jacket Material :	CPE
Outdoor (Y N) :	Yes
Temperature :	90°C
O.D. (Inches Nom.) :	0.976
Outer Diameter (MM Nom.) :	24.79
Voltage :	600 Volts
Approvals :	(UL) Type TC-ER RoHs Direct Burial
Weight /LBS per 1000FT:	905
Item Type :	Tray Cable XLP-CPE Direct Burial

*: * Ampacities are based on Table 310.15 (B)(16) of the NEC 2014 Edition

**: All data and dimensions are nominal and subject to industry standards and may vary according to plant of manufacture.

***: Data is provided for informational purposes and does not create a binding obligation nor liability to the seller. Data can change without notice.
© All Rights Reserved Ramcorp Technologies LLC.